



MAX PLANCK INSTITUTE
FOR DYNAMICS OF COMPLEX
TECHNICAL SYSTEMS
MAGDEBURG



COMPUTATIONAL METHODS IN
SYSTEMS AND CONTROL THEORY

morgen (1.0)

Model Order Reduction for Gas and Energy Networks

C. Himpe, S. Grundel

CSC

Supported by:



Federal Ministry
for Economic Affairs
and Energy



<https://git.io/morgen>



morgen (german for: tomorrow)

- **M**odel
- **O**der
- **R**eduction

for **G**as

and **E**nergy

- **N**etworks



- Testing model-solver-reductor combinations
- Comparing models, solvers, or reducers
- Benchmarking reducers
- Prototyping algorithms
- Uncertainty quantification



- Open-source (BSD-2-Clause)
- High-Level (MATLAB and OCTAVE)
- Modular (Six modules)
- Configurable (Three-level configuration)
- Extensible (Contributions welcome)



1. Models
2. Solvers
3. Reductors
4. Networks
5. Tests
6. Tools



Implemented:

- `ode_mid` – midpoint discretization
- `ode_end` – endpoint discretization (port-Hamiltonian)

```
discrete = model(network, config);
```

`discrete` **Structure:**

- | | |
|--|---|
| ■ <code>.E</code> – Mass matrix function | ■ <code>.J</code> – Vector field Jacobian |
| ■ <code>.A</code> – System matrix | ■ <code>.x0</code> – Initial state |
| ■ <code>.B</code> – Input matrix | ■ <code>.nP</code> – Number of pressure states |
| ■ <code>.C</code> – Output matrix | ■ <code>.nQ</code> – Number of mass-flux states |
| ■ <code>.f</code> – Nonlinear vector field | ■ <code>.nPorts</code> – Number of ports |



Implemented:

- `imex1` – 1st Order Implicit-Explicit (Euler-Euler)
- `imex2` – 2nd Order Implicit-Explicit (Runge-Kutta)
- `generic` – 2nd Order Adaptive Rosenbrock (`ode23s`)
- `rk4` – “Classic” 4th Order Explicit Runge-Kutta

```
solution = solver(discrete,scenario,config);
```

`solution` **Structure:**

- | | |
|--|---|
| ■ <code>.t</code> – Time instances | ■ <code>steady_z0</code> – Mean compressibility |
| ■ <code>.u</code> – Input time series | ■ <code>steady_error</code> – Steady-state error |
| ■ <code>.y</code> – Output time series | ■ <code>steady_iter1</code> – Algebraic Iterations |
| ■ <code>.runtime</code> – Solver runtime | ■ <code>steady_iter2</code> – Differential Iterations |



Implemented:

- `pod_r` – Structured Proper Orthogonal Decomposition
 - `eds_ro`, `eds_wx`, `eds_wz`,
`eds_ro_l`, `eds_wx_l`, `eds_wz_l` – Structured Dominant Subspaces Variants
 - `bpod_ro`,
`bpod_ro_l` – Structured Balanced Proper Orthogonal Decomposition
 - `ebt_ro`, `eds_wx`, `eds_wz`,
`ebt_ro_l`, `eds_wx_l`, `eds_wz_l` – Structured Balanced Truncation Variants
 - `gopod_r` – Goal-Oriented Proper Orthogonal Decomposition
 - `ebg_ro`, `eds_wx`, `eds_wz`,
`ebg_ro_l`, `eds_wx_l`, `eds_wz_l` – Structured Balanced Gains Variants
 - `dmd_r` – Dynamic Mode Decomposition Galerkin
- `[proj,name] = reducer(solver,discrete,scenario,config);`
- `spaces` – Cell array of projectors
 - `name` – Full name of reducer



Network and scenario data:

- Network data stored as decorated edge list in CSV format (`.net`).
- Scenario data stored as key-value pairs in INI format (`.ini`).
- Network base name determines associated scenario folder name.
- Each network has minimally a `training.ini` scenario.

Types of tests:

- Prefix `sim_` – Simulate scenario by a model-solver combination.
- Prefix `mor_` – Reduce and test model-solver-reductor combination.



Available:

- `xml2net` – Convert *GasLib* .xml to `morgen .net`
- `json2net` – Convert *MathEnergy* .json to `morgen .net`
- `csv2net` – Convert *SciGRID_gas* .csv to `morgen .net`
- `vf2kgs` – Convert volume flow to mass flow in kg/s
- `psi2bar` – Convert pressure from psi to bar
- `cmp_friction` – Compare friction factors
- `cmp_compressibility` – Compare compressibility factors
- `randscen` – Generate random scenario from training scenario



Available:

- optional arguments (`varargin`)
- configuration file (`morgen.ini`)
- fallback via hard-coded default values



```
R = morgen(network_id,scenario_id,model_id,solver_id,redutor_ids,varargin);
```

{string} network_id – Network file (.net) base name

{string} scenario_id – Scenario file (.ini) base name

{string} model_id – Model function name

{string} solver_id – Solver function name

{cell} redutor_ids – Array of redutor names

{string} varargin – Adhoc configuration arguments ('key=val')



- Currently, all reducers use emgr: <https://gramian.de>
- A template model, solver and reductor are available.
- This is research software!



morgen – **M**odel **O**rders **R**eduction for **G**as and **E**nergy **N**etworks

→ <https://git.io/morgen> ←

C. Himpe, S. Grundel, P. Benner:

Model Order Reduction for Gas and Energy Networks.

arXiv: 2011.12099, 2021. <https://arxiv.org/abs/2011.12099>

Acknowledgment:

Supported by the German Federal Ministry for Economic Affairs and Energy, in the joint project: “**MathEnergy** – Mathematical Key Technologies for Evolving Energy Grids”, sub-project: Model Order Reduction (Grant number: 0324019**B**).